Technical Data Sheet

LUBRATECH ATF DEXRON VI



Automatic Transmission Fluid

PRODUCT DESCRIPTION

LUBRATECH ATF DEXRON VI is a supreme performance long life automatic transmission fluid. This fluid is formulated with exceptional quality synthetic base oils and advanced additive technology to provide outstanding oxidation resistance, friction durability, wear protection. It also provides improved performance in older GM vehicles, wherever DEXRON is specified.

PROPERTIES

- Enhanced performance in both new and older transmissions
- Optimised frictional properties prevent clutch shudder and enable smooth gear shifting & extended clutch durability
- Exceptional viscosity profile, improved torque transfer and low viscosity of this oil help in improving fuel economy
- Enhanced foam control maintains responsive shifts and reduces wear on bearings, bushings and gears
- Excellent low temperature fluidity leads to easy pumping in the hydraulic circuits
- Special rust and corrosion inhibitors protect critical parts against rust and corrosion throughout the service life
- Longer transmission life

MEETS AND CERTIFICATES

- General Motors Dexron VI
- MB 236.15, MB 236.16, MB 236.81
- Allison C4
- MAN 339 type V-2 & Z-3
- Voith 55.6336

- ZF TE-ML-09, -03D,-4D, -14C,-16M, -17C, ZF TE-ML-05L
- JASO 1A LV
- Honda ATF Type 3.1

TECHNICAL INFORMATION

'n	atution of	Lubricant	4	
ī	Kinematic Viscosity	Viscosity Index	Flash Point	Pour Point
	100°C (cSt)	(min)	(min) (°C)	(max) (°C)
	5,6 – 9,3	153	210	-41

Values can change for each production.

STORAGE

- Keep away from sources of ignition, store this product in a dry location where it can be protected from the elements.
- Store in tightly closed, properly ventilated containers away from heat, sparks, open flame.
- All packs should be on pallets and maximum 2 rows on top of each other should be placed.
- Packs should be kept clean and dust should be taken care of with clean cloth.
- In open lubrication processes, tray should be kept under drainages. Empty packs should not be used except storage of lubricants.

WARNINGS and RECOMMENDATIONS

- Waste products should not be spilled to any water sources or sewage or to dustbin.
- Contact with the product could cause skin problems, sterile gloves should be used.
- If it contacts with the skin, that region should be washed with water and soap.
- Doctor be should contacted in case of any skin irritation and redness.

The information in this TDS is obtained from reliable sources of OEM. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This TDS was prepared and is to be used only for this product. If the product is used as a component in another product, this information may not be applicable.

Product Name: LUBRATECH ATF DEXRON VI First Published: 27.03.2019

First Published : 27.0:

FR.31