

PRODUCT DESCRIPTION

LUBRATECH POWERTECH 10W-40 is high performance heavy duty motor oil formulated with high quality synthetic base oils and advanced additives technology. It can be used in all four seasons and provide maximum motor cleanliness. Suitable for heavy duty diesel vehicles and machinery. It provides low emission levels and designed to provide improved performance and service life in after treatment systems including diesel particulate filters (DPF).

PROPERTIES

- Longer oil change intervals and decreased fuel consumption
- Protects the engine from wear, rust and corrosion
- Minimised deposit and ash in even higher temperatures
- Long drain intervals, it meets leading OEM specifications
- Due to low emission levels, it protects the environment

MEETS AND CERTIFICATES

- API CJ-4
- ACEA E6/E7-12
- DEUTZ DQC III-10 LA
- MAN 3477 / MAN 3271-1
- MTU TYPE 3.1
- CAT ECF-1-a
- SCANIA LDF-2
- MB 228.51

APPROVALS

- VOLVO VDS-3
- RENAULT VI RLD-2
- MACK EO-N

TECHNICAL INFORMATION

Kinematic Viscosity 100°C (cSt)	Viscosity Index (min)	Flash Point (min) (°C)	Pour Point (max) (°C)
12,5 – 16,3	150	240	-37

Values can change for each production.

STORAGE

- Keep away from sources of ignition, store this product in a dry location where it can be protected from the elements.
- Store in tightly closed, properly ventilated containers away from heat, sparks, open flame.
- All packs should be on pallets and maximum 2 rows on top of each other should be placed.
- Packs should be kept clean and dust should be taken care of with clean cloth.
- In open lubrication processes, tray should be kept under drainages. Empty packs should not be used except storage of lubricants.

WARNINGS and RECOMMENDATIONS

- Waste products should not be spilled to any water sources or sewage or to dustbin.
- Contact with the product could cause skin problems, sterile gloves should be used.
- If it contacts with the skin, that region should be washed with water and soap.
- Doctor be should contacted in case of any skin irritation and redness.

The information in this TDS is obtained from reliable sources of OEM. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this information may not be applicable.