

PRODUCT DESCRIPTION

LUBRATECH MOTOTECH POWER 2T is quality lubricant suitable for use in 2-stroke gasoline engines. It can be mixed with gasoline in the engines of 2-stroke air cooled motorcycles, and scooters. Fuel/oil mixing ratio should be decided according to the original equipment recommendations.

PROPERTIES

- Excellent lubricity protects against piston scuffing and premature wear of engine components
- Proven additive technology controls engine and exhaust system deposits
- Low ash formula prevents pre-ignition and spark plug fouling
- Improves combustion efficiency
- Thanks to good mixing ability with gasoline, it enables stable homogeneous mixture even at low ambient temperatures

MEETS AND CERTIFICATES

- API: TC / W2-W3
- JASO FB

TECHNICAL INFORMATION

Kinematic Viscosity 100°C (cSt)	Viscosity Index (min)	Flash Point (min) (°C)	Pour Point (max) (°C)
7,5-11,3	110	200	-24

Values can change for each production.

STORAGE

- Keep away from sources of ignition, store this product in a dry location where it can be protected from the elements.
- Store in tightly closed, properly ventilated containers away from heat, sparks, open flame.
- All packs should be on pallets and maximum 2 rows on top of each other should be placed.
- Packs should be kept clean and dust should be taken care of with clean cloth.
- In open lubrication processes, tray should be kept under drainages. Empty packs should not be used except storage of lubricants.

WARNINGS and RECOMMENDATIONS

- Waste products should not be spilled to any water sources or sewage or to dustbin.
- Contact with the product could cause skin problems, sterile gloves should be used.
- If it contacts with the skin, that region should be washed with water and soap.
- Doctor be should contacted in case of any skin irritation and redness.

The information in this TDS is obtained from reliable sources of OEM. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This TDS was prepared and is to be used only for this product. If the product is used as a component in another product, this information may not be applicable.