

# Technical Data Sheet

## LUBRATECH LONG LIFE 15W-40



### Heavy Duty Motor Oil

#### PRODUCT DESCRIPTION

LUBRATECH LONG LIFE 15W-40 is a high performance heavy duty motor oil formulated with high quality base oils and advanced additives technology. It can be used in all four seasons and provide maximum motor cleanliness. Suitable for heavy duty diesel vehicles and machinery.

#### PROPERTIES

- Minimised deposit and ash in even higher temperatures.
- Prevents the engine from wear, oxidation and corrosion in severe conditions.
- Due to high viscosity index it is resistant to temperature changes.
- Long drain intervals, it meets leading OEM specifications.

#### MEETS AND CERTIFICATES

- API CI-4/SL
- ACEA E4 / E7-16
- ACEA A3/B4-16
- JASO DH-1
- MAN M 3275-1
- MTU Type 2
- DEUTZ DQC III-10
- ALLISON C4
- MB 228.3
- CAT ECF-1a
- CUMMINS CES 20076/77/71/72
- CUMMINS CES 20078

#### APPROVALS

- VOLVO VDS-3
- RENAULT VI RLD-2
- MACK EO-N

#### TECHNICAL INFORMATION

Kinematic Viscosity 100°C (cSt)	Viscosity Index	Flash Point (°C)	Pour Point (°C)
12,5 – 16,3	140	240	-24

Values can change for each production.

#### STORAGE

- Keep away from sources of ignition, store this product in a dry location where it can be protected from the elements.
- Store in tightly closed, properly ventilated containers away from heat, sparks, open flame.
- All packs should be on pallets and maximum 2 rows on top of each other should be placed.
- Packs should be kept clean and dust should be taken care of with clean cloth.
- In open lubrication processes, tray should be kept under drainages. Empty packs should not be used except storage of lubricants.

#### WARNINGS and RECOMMENDATIONS

- Waste products should not be spilled to any water sources or sewage or to dustbin.
- Contact with the product could cause skin problems, sterile gloves should be used.
- If it contacts with the skin, that region should be washed with water and soap.
- Doctor be should contacted in case of any skin irritation and redness.

The information in this TDS is obtained from reliable sources of OEM. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this information may not be applicable.