

PRODUCT DESCRIPTION

LUBRATECH MOTORRAD SYNTH 4T 10W-40 is a 4-stroke synthetic based motorcycle oil. It is blended with premium quality synthetic base oils and advanced additive technology. It is used in high rev, 4-stroke motorcycles (air or water cooled). Also suitable for European and Japanese manufacturers where JASO MA2 and API SL is recommended.

PROPERTIES

- Good wear and corrosion protection
- Thermal and oxidation stability
- Excellent wet brake clutch performance

MEETS REQUIREMENTS

- API SL
- JASO MA-2

Property	JASO MA2
Dynamic Friction Characteristic Index (DFI)	≥1.8 and <2.5
Static Friction Characteristic Index (SFI)	≥1.7 and <2.5
Stop Time Index (STI)	≥1.9 and <2.5

TECHNICAL INFORMATION

Kinematic Viscosity 100°C (cSt)	Viscosity Index (min)	Flash Point (min) (°C)	Pour Point (max) (°C)
12,5 – 16,3	140	220	-30

Values can change for each production

STORAGE

- Keep away from sources of ignition, store this product in a dry location where it can be protected from the elements.
- Store in tightly closed, properly ventilated containers away from heat, sparks, open flame.
- All packs should be on pallets and maximum 2 rows on top of each other should be placed.
- Packs should be kept clean and dust should be taken care of with clean cloth.
- In open lubrication processes, tray should be kept under drainages. Empty packs should not be used except storage of lubricants.

WARNINGS and RECOMMENDATIONS

- Waste products should not be spilled to any water sources or sewage or to dustbin.
- Contact with the product could cause skin problems, sterile gloves should be used.
- If it contacts with the skin, that region should be washed with water and soap.
- Doctor be should contacted in case of any skin irritation and redness.

The information in this TDS is obtained from reliable sources of OEM. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this information may not be applicable.